



## Mid and Long Link Chain

Any chain with link dimensions greater than a short link chain of the same diameter is classed as long link. It is common practice, however to use the terms mid link or open link to describe links with inside dimensions around 4 x 1.5 times the diameter – e.g. 16mm dia. x 64 x 24.

Long link is made in all strength grades, usually to commercial standards, and is popular for applications where it is desirable to insert components into the links. There is no British Standard for general purpose long link chain. The table below details our normal stock sizes. Other sizes are frequently available or can be made to order. The chain is supplied self colour or with various surface finishes.

Size (steel diameter)	inside link dimensions		Grade 30 maximum service load	Grade 40 maximum service load	Grade 80 maximum service load	approx. weight per metre
	I/L approx.	I/W approx.				
Safety factor			5:1	5:1	4:1	
mm	mm	mm	tonnes	tonnes	tonnes	Kg.
6.5	36	14	0.42	-	-	0.79
8	50	16	0.64	0.80	-	1.10
9	53	15	-	-	2.5	1.40
9.5	50	19	0.91	1.1	-	1.67
10	40	15	1.0	-	3.2	1.95
11	63	18	-	-	3.8	2.10
12.5	57	22	1.5	1.9	-	3.00
13	55	19.5	-	-	5.4	3.28
13	80	20	-	-	5.4	2.85
16	64	24	2.5	3.2	8.0	4.97
16	100	26	2.5	3.2	8.0	4.40
19	76	28	3.6	4.5	11.5	6.90
19	100	28	3.6	4.5	11.5	6.40
22	111	33	4.8	6.1	-	8.70
26	104	39	-	8.5	-	13.30

For up to date prices and availability please contact our sales office who will be happy to quote for your specific enquiry.

Tel. [01384-636233](tel:01384-636233) Fax [01384-634289](tel:01384-634289) Email [sales@bradneychain.co.uk](mailto:sales@bradneychain.co.uk)